

COLOR & ILLUMINATION



3M Graphic Films

- 3M 3730-73L Dark Red translucent film
- 3M 3630-22 Black translucent film
- 3M 3660M matte overlaminate film

3M Flexible Substrates

- 3M Envision FS-1
- 3M Panagraphics III

Painted Finishes

- White, satin finish
- To be determined
- Pantone® 200 C Red

LED Illumination

All internally illuminated signage to be illuminated using GE 7100K white LED's. LED's to be populated for even and consistent illumination to ensure no hot spots or shadows on the sign faces.






STANDARD SIGN SIZES





These are on the building



PM28

Standard Sign Sizes
Scale: 3/16" = 1'-0"

Standard signs are available in single-faced and double-faced options.

Standard signs feature bright, reliable, energy-efficient LED illumination.


Replacement faces for standard signs are available.





HI-RISE SIGNS





Hi-Rise Cabinet Specifications:

- Frame construction: 25" deep reverse angle frame
- Retainer type: bleed
- Skin: .063" aluminum
- Exterior finish: satin white
- Interior finish: reflective white
- Illumination: GE 7100K white LED's
- U.L. Listed/CUL Listed
- Service: removable doors
- Mounting: plate/match plate

Hi-Rise Face Specifications:

 - 3M Envision FS-1 flexible face with 1st surface vinyl decoration:

3M 3730-73L Dark Red translucent film 3M 3660M matte overlaminate film

Pole Specifications:

- Poles to be painted satin white


NOTE: Hi-rise sign must be the largest standard sign allowed by local sign code.






MONUMENT SIGNS







Scale: 3/16" = 1'-0"

Mid-Rise Cabinet Specifications:

- Frame construction: 25" deep reverse angle frame
- Retainer type: bleed
- Skin: .063" aluminum
- Exterior finish: satin white
- Interior finish: reflective white
- Illumination: GE 7100K white LED's
- U.L. Listed/CUL Listed
- Service: removable doors
- Mounting: plate/match plate

Mid-Rise Face Specifications:

 3M Envision FS-1 flexible face with 1st surface vinyl decoration;

3M 3730-73L Dark Red translucent film 3M 3660M matte overlaminate film

Pole Cover Specifications:

- Frame construction: 20" deep aluminum angle frame
- Skin: .080" aluminum
- Exterior finish: paint to match Sherwin Williams SW 7072 Online, satin finish
- Reveal: aluminum tube
- Reveal finish: paint Pantone® 200 C red
- Reveal illumination: reveals to be illuminated using GE red LED's inside pole cover section above reveal. Red illumination to shine down on reveal from above to illuminate.

NOTE: Monument sign must be the largest standard sign allowed by local sign code.





EXTERIOR BUILDING SIGNS







Wall Logos Scale: 3/16"= 1'-0" Scale: 3/16"= 1'-0"

Wall Logo Cabinet Specifications:

- Frame construction: 14" deep reverse angle frame
- Retainer type: bleed
- Skin: .063" aluminum
- Back: 24 gauge steel
- Exterior finish: satin white
- Interior finish: reflective white
- Illumination: GE 7100K white LED's
- U.L. Listed/CUL Listed
- Service: removable skin
- Mounting: flush wall mount

Wall Logo Face Specifications:

 3M Envision FS-1 flexible face with 1st surface vinyl decoration:

3M 3730-73L Dark Red translucent film 3M 3660M matte overlaminate film





PM-DN



LENGTH VARIES BASED ON NUMBER OF CHARACTERS


PETERBILT OF CITY NAME

Dealer Name Channel Letters

Scale: 3/16" = 1'-0"

PETERBILT OF CITY NAME

Nighttime View Scale: 3/16" = 1'-0"



End View Scale: 3/4" = 1'-0"

Dealer Name Channel Letters:

- Letter return: .063" aluminum, 5" deep
- Face: .125" aluminum
- Back: .150" clear polycarbonate
- Exterior finish: satin black
- Interior finish: reflective white
- Illumination: GE 7100K white LED's
- U.L. Listed/CUL Listed
- Power supply location: remote mounted
- Mounting: pin-mount 1" off wall





CUSTOMER ENTRANCE CHANNEL LETTERS












Amenity Channel Letters
Scale: 1/4" = 1'-0"





Customer Entrance Channel Letters:


- Letter return: .040" aluminum, 3" deep
- Retainer: 1" black trim cap
- Face: .118" day/night acrylic
- Back: .063" aluminum
- Exterior finish: satin black
- Interior finish: reflective white
- Illumination: GE 7100K white LED's
- U.L. Listed/CUL Listed
- Power supply location: remote mounted
- Mounting: flush wall mount






ENTRANCE FEATURE









Entrance Feature Specifications:

- Construction: aluminum angle frame
- Skin: 4mm Silver Metallic ACM
- Mounting: Base plate (not to be attached to building)
- Top horizontal piece to mount via dual plate/match plate
- Grill feature: .063" perforated aluminum painted metallic silver attached to 1 1/2" X 3/16" aluminum angle (perimeter) and 1" X 2" X 1/8" aluminum tube on front side where aluminum sheets meet. Tube and angle painted metallic silver.
- "Sales & Leasing" band:

Construction: aluminum angle

Skin: .080" aluminum painted Pantone® 200 C

red

Face: .125" routed aluminum painted Pantone®

200 C red

Copy: 3/4" clear acrylic push-thru letters with 1st and 2nd surface decoration:

3M 3635-70 white diffuser film (2nd

surface)

3M 3630-20 white film (1st surface)

Bottom of "Sales & Leasing" band to have 3

LED recessed down lights.

